

# TECH DATA SHEET

# PROJOINT BLACK LIMESTONE

# & DARK STONE RESTORER

PROSEAL TECHNOLOGY



## PREPARATION:

SUBSTRATES SHOULD BE SOUND, CLEAN AND FREE FROM DIRT, DUST, OIL, ETC AND MUST BE TOTALLY DRY. WE RECOMMEND CLEANING WITH PROJOINT PAVING & DRIVEWAY CLEANER PRIOR TO APPLICATION AND LEAVE TO DRY FOR AT LEAST TWO DAYS. AS WITH ALL SEALANTS, TEST ON A SMALL INCONSPICUOUS AREA BEFORE FULL APPLICATION. THE SEALER IS SUPPLIED READY FOR USE AND SHOULD BE APPLIED WHEN THE SURFACE TEMPERATURE OF THE PAVING IS BETWEEN 5°C AND 25°C. AS A GUIDE, THE STONE SHOULD BE COOL TO THE TOUCH.

## APPLICATION INSTRUCTIONS:

**1:** SHAKE CONTAINER WELL BEFORE APPLICATION. **1A:** WEARING APPROPRIATE PPE, APPLY PROJOINT PROJOINT BLACK LIMESTONE & DARK STONE RESTORER IN A LIGHT EVEN LAYER USING A FOAM ROLLER OR PAINT BRUSH, ENSURING EXCESS IS REMOVED. **2:** ALLOW TO DRY (UP TO 4 HOURS DRYING TIME) **2A:** IF REPEAT APPLICATION IS REQUIRED FOR FURTHER ENHANCED COLOUR & PROTECTION, PLEASE ALLOW THE FIRST COAT TO DRY AND THEN ADD A SECOND LIGHT COAT. **3:** ALL TOOLS/EQUIPMENT SHOULD BE THOROUGHLY CLEANED WITH WATER. **NOTE:** 2 LIGHT COATS ARE BETTER THAN 1 HEAVY COAT.

**IMPORTANT:** ALWAYS TEST IN A HIDDEN AREA PRIOR TO USE AND ONLY PROCEED WHEN SATISFIED WITH THE RESULTS. THE TECHNICAL INFORMATION SUPPLIED IS BASED ON DATA OBTAINED BY OUR OWN RESEARCH AND IS CONSIDERED ACCURATE. HOWEVER, NO LIABILITY IS ACCEPTED FOR ANY LOSS OR DAMAGE ARISING DIRECTLY OR INDIRECTLY FROM THE USE OF OUR PRODUCTS, OR FROM THE INFORMATION GIVEN IN PUBLICATIONS. PROSPECTIVE USERS SHOULD THEREFORE SATISFY THEMSELVES BY APPROPRIATE TRIALS THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE. DO NOT DISCHARGE WASTE INTO DRAINS OR RIVERS.

SYSTEM	WATER BASED DARK STONE COLOUR RESTORER
STORAGE	STORE COOL, AND DRY AT TEMPERATURES BETWEEN 5°C AND 25°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1LTR AND 5LTR CONTAINERS
DRYING TIME	UP TO 4 HOURS IN DRY AMBIENT CONDITIONS
CURING TIME	24 HOURS IN DRY AMBIENT CONDITIONS
COVERAGE	UP TO 30SQM PER LTR DEPENDENT ON POROSITY



WARNING



## KEY FACTS:

- ✓ COLOURED IMPREGNATING SEALER DESIGNED TO PERMANENTLY REJUVENATE AND RESTORE DARK PAVING
- ✓ SUITABLE FOR ALL TYPES OF FADED STONE INCLUDING LIMESTONE, MARBLE, SLATE OR CONCRETE
- ✓ RESISTS DIRT, GRIME AND ALGAE
- ✓ SEALS AND PROTECTS
- ✓ READY TO USE AND ULTRA HIGH COVERAGE RATE (UP TO 30SQM PER LTR)

**KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS**

**MAY PRODUCE AN ALLERGIC REACTION**

**HAZARD STATEMENTS:** H332 Harmful if inhaled. H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS:** P102 Keep out of reach of children. P260 Do not breathe fumes/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call POISON CENTER/ doctor if you feel unwell. P501 Dispose of contents/container to hazardous or special waste collection point.

**STORAGE:** Store in a cool, well ventilated area. Keep container tightly closed. Unopened containers can be stored in these conditions for up to 1 year. **Protect from frost.**

**COVERAGE:** This product covers approximately 30m<sup>2</sup> per litre depending on substrate porosity.

**A FULL SAFETY DATASHEET IS AVAILABLE ON REQUEST**

## BRUTE STRENGTH PAVING PRODUCTS

