

TECH DATA SHEET

PROJOINT ECO820

WATER BASED INVISIBLE PAVING SEALER



PRODUCT INFORMATION

PROJOINT ECO820 WATER BASED INVISIBLE SEALER is designed for all types of porcelain, natural stone or concrete paving whether it is inside or out.

PROJOINT ECO820 WATER BASED INVISIBLE SEALER can be applied to stone, concrete or porcelain paving prior to grouting to minimise any grout haze or resin sheen, or alternatively paving can be treated once the grout/jointing material has been applied and fully cured.

The water based sealer impregnates the surface of the paving to give an invisible and lasting protection against dirt, staining and natural weathering.

DIRECTIONS FOR USE

Paving should be sound, clean and free from dirt, dust, oil, etc. Surfaces can be damp prior to application, but a better seal would be achieved if the paving is dry. We recommend cleaning with Nexus Paving & Driveway Cleaner prior to application.

PROJOINT ECO820 WATER BASED INVISIBLE SEALER is designed as an invisible coating but may darken very light surfaces slightly. As with all sealants, test on a small inconspicuous area before full application.

The sealer is supplied ready for use and should be applied when the surface temperature of the paving is between 5°C and 25°C. As a guide, the stone should be cool to the touch. Shake the container well prior to use. Application may be made by brush, roller or spray (ensuring appropriate PPE is worn). Apply a complete, even coat over the whole surface ensuring any excess is removed - allow to dry for 30 minutes.

Apply a second even coat and leave to cure. Dependent on temperature, this second coat should be fully cured in around 1 hour (an extra coat may be required on porous paving).

HEALTH AND SAFETY ADVISORY

CONTAINS: 2-METHYLISOTHIAZOL-3(2H)-ONE
May cause an allergic skin reaction. Keep out of reach of children and animals.

Wear protective gloves/protective clothing/ eye protection/face protection.

IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

STORAGE: The PROJOINT PRE-GROUT PAVING SEALER should be stored in sealed containers in a cool, dry and frost-free environment, protected from extremes of temperature.

SYSTEM	WATER BASED INVISIBLE PAVING SEALER FOR NATURAL STONE, CONCRETE AND PORCELAIN PAVERS
STORAGE	STORE IN A COOL, DRY, AND FROST FREE ENVIRONMENT AT TEMPERATURES BETWEEN 5°C AND 30°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1 LITRE, 25 LITRE & 25 LITRE TUBS DELIVERED ON SHRINK-WRAPPED PACKAGING
PALLET QUANTITY	N/A
COVERAGE	UP TO 15M ² PER LITRE ON NATURAL STONE, 30M ² PER LITRE ON PORCELAIN
COLOURS	N/A
WALK ON CURING TIME	IMMEDIATELY AFTER SURFACE DRY
FULL STRENGTH	N/A
SUB BASE REQUIREMENT	N/A

KEY FACTS:

- ✓ HIGH STRENGTH INVISIBLE SEALER THAT IS FAST AND EASY TO USE
- ✓ IMPREGNATES THE PAVING SURFACE FOR LONG LASTING PROTECTION
- ✓ WATER BASED AND CAN BE USED ALL YEAR ROUND
- ✓ HIGH COVERAGE RATE FOR STONE AND PORCELAIN PAVING
- ✓ IDEAL FOR ALL TYPES OF TEXTURED PORCELAIN TILE SURFACES
- ✓ PERFECT FOR ALL TYPES OF NATURAL STONE PAVING

APPROXIMATE COVERAGE PER LITRE

Depending on substrate porosity, this product covers up to:

15m² per litre when applied to natural stone or concrete
30m² per litre on porcelain.

'innovative invisible sealer for both porcelain & stone...'

BRUTE STRENGTH PAVING PRODUCTS

